# **PCT**

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



#### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:
C07C 2/32, C10G 50/02

(11) International Publication Number: WO 00/34211

(43) International Publication Date: 15 June 2000 (15.06.00)

(21) International Application Number: PCT/GB99/04010

(22) International Filing Date: 1 December 1999 (01.12.99)

(30) Priority Data: 9826755.2 4 December 1998 (04.12.98) GB

(71) Applicant (for all designated States except US): BP CHEM-ICALS LIMITED [GB/GB]; Britannic House, 1 Finsbury Circus, London EC2M 7BA (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): JONES, Michael, David [GB/GB]; 23 Westwood Road, Beverley, East Yorkshire HU17 8EN (GB). GRIMM, Seifgried [DE/CH]; Neudorfstrasse 15, CH-8050 Zurich (CH). KEIM, Wilhelm [DE/DE]; Brusseler Ring 99, D-52074 Aachen (DE). WASSERSCHEID, Peter [DE/DE]; Grevenbroicher Strasse 2, D-50829 Koln (DE).

(74) Agent: COLLINS, Frances, Mary; BP International Limited, Patents & Agreements, Chertsey Road, Sunbury on Thames, Middlesex TW16 7LN (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### **Published**

With international search report.

(54) Title: OLIGOMERISATION PROCESS

#### (57) Abstract

A process for the oligomerisation of C8–C36 alpha-olefins to give a polyolefin product comprising trimer which process comprises contacting the C8–C36 alpha-olefin with a catalyst in a solvent at a temperature below 20 °C wherein the catalyst comprises a complex of a chromium compound and a 1,3,5-triazacyclohexane and the polyolefin product comprises at least 70 mole% of trimer. The polyolefin product can be catalytically hydrogenated to lubricating oils.

# FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Јарал	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
СН	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China .	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		,
EE	Estonia	LR	Liberia	SG	Singapore		

## **OLIGOMERISATION PROCESS**

This invention relates to a process for oligomerising olefins and, in particular, to a process for the trimerisation of olefins using catalyst compositions comprising a source of chromium.

Methods of oligomerising unsaturated hydrocarbons including *inter alia* trimerising olefins using chromium containing catalysts are well known. For example, EP-A-0780353 describes a process for oligomerising olefins using a catalyst system comprising a chromium source, a pyrrole-containing compound and a metal alkyl. The catalyst system is supported on an inorganic oxide. Suitable trimerisation olefins are disclosed as C2-C30 olefins e.g ethylene, propylene, the butenes, 1-pentene, 4-methyl-1-pentene, 1-hexene, 1-heptene, the four normal octenes, the four normal nonenes, vinylcyclohexane and mixtures thereof. More specifically, this reference discloses the trimerisation of ethylene to 1-hexene, 1,3-butadiene to 1,5-cyclooctadiene, or the co-trimerisation of ethylene and hexene to form 1-decene or 1-tetradecene.

5

10

15

20

US 5137994 describes a method of producing a copolymer of ethylene and 1-hexene in which ethylene is simultaneously trimerised to 1-hexene which is copolymerised with further aliquots of ethylene in the presence of a bis-triarylsilyl chromate compound.

US 5087789 describes the oligomerisation of propylene and/or ethylene in the presence of a chromium catalyst on an aluminophosphate support and a selectivity modifier.

In an article entitled "Selective Trimerization of Olefins with 1,3,5-Triazacyclohexane Complexes of Chromium" by Randolf D Köhn et al based on a

presentation at "The XVIIIth International Conference on Organometallic Chemistry" held in Munich, Germany on 16-21 August 1998, the authors propose a mechanism for the trimerisation of 1-hexene using a 1,3,5-triazacyclohexane chromium catalyst activated with MAO.

5

10

15

20

25

30

Suprisingly, it has now been found that alpha-olefins having 8 to 36 carbon atoms can be oligomerised using a chromium based catalyst under specific reaction conditions to give a product predominating in trimers. The improved selectivity to trimers allows the product to be hydrogenated to lubricating oils.

Accordingly, the present invention provides a process for the oligomerisation of C8-C36 alpha-olefins to give a polyolefin product comprising trimer which process comprises contacting the C8-C36 alpha-olefin with a catalyst in a solvent at a temperature below 20°C wherein the catalyst comprises a complex of a chromium compound and a 1,3,5-triazacyclohexane and the polyolefin product comprises at least 70 mole% of trimer.

By trimer is meant a polyolefin product formed by the reaction of three alphaolefin molecules. For example, 1-octene, 1-decene, 1-dodecene can trimerise to give olefin products containing 24, 30 and 36 carbon atoms respectively.

The alpha-olefin that may be trimerised according to the process of the present invention preferably has 10 or more carbon atoms and more preferably has from 10-30 carbon atoms. The alpha-olefin may be a straight or branched chain olefin. Specific examples of suitable alpha-olefins include octene-1, decene-1, dodecene-1, hexadecene-1, octadecene-1 and eicosene.

The process of the present invention selectively converts an alpha-olefin to trimers. The selective conversion of alpha-olefin to trimer is preferably at least 80 mol% e.g 80-99 mol%, preferably at least 90 mol%, more preferably at least 95 mol%, especially at least 98 mol%. The yields of dimers, tetramers or other oligomers are reduced compared with known oligomerisation processes.

The trimerisation catalyst used in the process of the present invention is a complex of a chromium compound and a 1,3,5-triazacyclohexane (hereinafter referred to as a chromium/triazacyclohexane catalyst). Preparation of such a complex is illustrated in the reaction scheme given below:-

$$R-NH_{2} + CH_{2}O$$

$$+$$

$$(THF)_{3}CrCl_{3}$$

$$R = N$$

5

10

15

The 1,3,5-triazacyclohexane may be prepared by known processes in the art e.g by reacting a primary amine with formaldehyde. In the above reaction scheme the R group of the primary amine is suitably a hydrocarbyl group, such as an alkyl, cycloalkyl, aryl, alkaryl or aralkyl group. The hydrocarbyl group may have from 6 to 12 carbon atoms. Preferably, the hydrocarbyl group is selected from a dimethyl hexyl, n-octyl, methyl benzyl, dimethyl undecanyl and n-dodecanyl group. The R group in the 1,3,5-triazacyclohexane compound will correspond to the R group in the reactant amine. For example, where n-octyl amine is used as the amine reactant i.e. where R is n-octyl, the 1,3,5-triazacyclohexane compound produced will be tri-n-octyl-1,3,5-triazacyclohexane. This 1,3,5-triazacyclohexane compound will hereafter be abbreviated as "R<sub>3</sub>TAC" for convenience.

To produce a chromium complex of R<sub>3</sub>TAC, R<sub>3</sub>TAC is reacted with a chromium compound in the presence of a solvent. Suitable chromium compounds include those chromium compounds having labile ligands e.g. chromium halides such as chromium chlorides having labile ligands. Suitable labile ligands are those capable of being replaced by R<sub>3</sub>TAC e.g tetrahydrofuran (THF). A suitable chromium compound is e.g. a complex of tetrahydrofuran with chromium trichloride ((THF)<sub>3</sub>CrCl<sub>3</sub>).

The solvent used for carrying out the reaction of R<sub>3</sub>TAC with the chromium compound is suitably a saturated hydrocarbon e.g. an aliphatic or aromatic hydrocarbon. Preferably, the saturated hydrocarbon is n-hexane, cyclohexane, benzene or toluene. The reaction may be carried out by refluxing a solution containing the chromium compound and the R<sub>3</sub>TAC. The resultant (R<sub>3</sub>TAC)chromium complex can be recovered by removing the solvent under vacuum and purifying the product by column chromatography. In the above reaction scheme (THF)<sub>3</sub>CrCl<sub>3</sub> is refluxed with R<sub>3</sub>TAC in e.g. equimolar amounts. The final chromium complex obtained and usable as a catalyst in the trimerisation process of the present invention is (R<sub>3</sub>TAC)CrCl<sub>3</sub>.

5

10

15

20

25

30

In the oligomerisation process of the present invention the alpha-olefin is contacted with a (R<sub>3</sub>TAC)chromium complex in the presence of a solvent. The catalyst may be activated by a modifier such as an alkyl alumoxane. Preferably, the alumoxane is methyl alumoxane (MAO). The solvent is suitably a saturated hydrocarbon or an aromatic solvent which does not actively participate in the reaction. Examples of solvents that may be used include n-hexane, n-heptane, cyclohexane, benzene, toluene and the xylenes. The contacting of the alpha-olefin and the chromium/triazacyclohexane catalyst is suitably carried out in an atmosphere inert under the process conditions such as eg nitrogen, argon and the like.

The oligomerisation process is carried out at relatively low temperatures of less than 20°C, suitably in the range from about -30°C to +20°C, preferably in the range from about -25 to +5°C, eg 0°C. At temperatures of the order of about 0°C, the trimerisation reaction goes through to completion with minimum deactivation of the chromium/triazacyclohexane catalyst.

The process of the present invention may be carried out by initially mixing a solution of the alpha-olefin and the chromium/triazacyclohexane catalyst, cooling this solution down and then gradually adding a solution of the catalyst modifier to this mixture whilst allowing the reaction mixture to warm up. During the warming up of the reaction mixture, it may change colour. The reaction mixture so formed is then neutralised by the addition of a strong acid, eg hydrochloric acid thereto. This results in a biphasic mixture comprising an aqueous and an organic phase. The biphasic mixture is separated eg using a centrifuge to recover the organic phase. The organic phase is dried and the mol % of trimers in the polyolefin product is determined e.g. by gas

chromatography.

5

10

15

25

30

The polyolefin product may then be catalytically hydrogenated to form lubricating oils. The hydrogenation may be carried out in solution. The catalyst may be any suitable hydrogenation catalyst, but is preferably, a palladium catalyst supported on activated carbon or a Raney nickel catalyst. The hydrogenation is suitably carried out at elevated pressure, eg from about 2000-10000 KPa, preferably from about 4500-8000 KPa. The hydrogenation reaction is suitably carried out at a temperature in the range from 15-200°C, preferably from about 30-70°C. The duration of the hydrogenation reaction may be a few minutes to several days. After the hydrogenation reaction is complete, the reaction mixture is cooled down, depressurised and the solvent used removed by vacuum distillation. The purity of the hydrogenated product can be determined by gas chromatography and the viscosity of the resulting lubricant measured by rotary viscosimetry.

The nature of the hydrocarbyl group, R, in a catalyst complex such as (R<sub>3</sub>TAC)CrCl<sub>3</sub> does not seem to affect or influence the selectivity to the desired trimers but it does have some effect on the distribution of isomers in the trimeric product. This enables the viscosity of the lubricating oil to be controlled.

The process of the present invention is further illustrated with reference to the following Examples:

### 20 A. Catalyst preparation

Chromium compounds L<sub>3</sub>CrCl<sub>3</sub> (where L<sub>3</sub> represents a tridentate ligand) are prepared by refluxing a solution of 0.1 mmol of a ligand L<sub>3</sub> and 0.1 mmol (THF)<sub>3</sub>CrCl<sub>3</sub> (where THF represents a tetrahydrofuranyl group) in toluene (10 ml) for 1 hour. The solvent is thereafter removed under vacuum and the resultant chromium complex of THF is purified using column chromatography.

## B. <u>Catalytic Experiments – General Procedure</u>

General: All experiments were carried out under argon as the inert gas atmosphere using standard Schlenk-technique.

Catalysis experiments: A chromium compound, L3CrX3 (where X is a halogen, 0.05 mmol) were dissolved in toluene (10 ml). An internal standard (n-heptane, cyclohexane) was added where indicated to the resulting purple solution. 10 ml of the olefin to be trimerised were added and the reaction mixture was cooled down to -25°C using a

cooling bath. An MAO (methyl alumoxane) solution (10% in toluene, 5.0 mmol, ex Witco) was added dropwise to the above purple solution via a syringe. The reaction mixture was then allowed to warm up in a second bath to reaction temperature of 0°C so as to commence the trimerisation reaction and was stirred for the specified reaction time.

During the warming up, the mixture turned from purple to blue to green. The green solution was active in trimerisation of olefins. As the solution turns into brownish the activity decreases.

Workup: An aqueous solution of 2N HCl (10 ml) was added to the reaction mixture. The resulting biphasic mixture comprising an aqueous and an organic phase was separated using a centrifuge. The organic phase was recovered, dried and the conversion was determined using Gas Chromatography.

The results of these Examples are summarised in Tables 1.1 and 1.2 below in which the following abbreviations have been used:

Me<sub>2</sub>Hex -

Dimethyl hexyl

15 Oc

10

n-Octyl

MAO

Methyl alumoxane

## Catalytic experiments

Table. 1.1: Reaction Conditions:

Run No.	1	2
ligand	(Oc) <sub>3</sub> TAC	(Me <sub>2</sub> Hex) <sub>3</sub>
		TAC
n (L <sub>3</sub> CrCl <sub>3</sub> )	0.05	0.05
(mmol)		
n MAO	5.00	5.00
(mmol)		
Standard (g)	n-heptane	n-heptane
	(0.45)	(1.01)
Starting	l-decene	1-dodecene
material	(10)	(20)
(ml)		
Solvent	toluene	toluene
(ml)	(10)	(9)
Temp. (°C)	0	0

Table.1.2 Results

Run No.	1				
Time (hours)	3	23	48		
m (dimer)	0	0.01	0.03		
m (trimer)	0.02	2.4	7.71		
m (tetramer)	0	0	0		
mol% trimer *	100	98	92		

Run No.	2				
Time (hours)	0.4	2	4	16.5	
m (dimer)	0	0	<0.01	<0.01	
m (trimer)	0.19	0.57	5.17	7.00	
m (tetramer)	0	0	0	0	
mol% trimer *	99	99	95	93	

\* based on the mol % of dimers and tetramers formed.

## Hydrogenation experiments:

5

10

15

Trimers of 1-decene and 1-dodecene prepared by the process of the present invention using different chromium/triazacyclohexane catalysts were hydrogenated to lubricating oils. Any solvents and internal standards used were removed from the trimer product by vacuum distillation. The residual organic phase was diluted with the same amount of cyclohexane and a hydrogenation catalyst (Pd on activated carbon, 5 % Pd, ex Fluka, 0.01 g for 1 g of the trimerised product) was suspended in the solution of the organic phase in an autoclave. The autoclave was pressurised with hydrogen (7000 KPa (70 bar)) and heated up to 50°C for 18 hours. The reaction mixture was then cooled down to room temperature, the autoclave was depressurised, and the solvent was removed by vacuum distillation. The purity of the products was determined by Gas Chromatography and the viscosity thereof by rotary viscosimetry (ISO 3104: 1994). The viscosity, viscosity index (VI) and pour points of the lubricating oils are given in Table 2 below. In

the Table the C36 alkene product was obtained by the trimerisation of 1-dodecene and the C30 alkene products were obtained by the trimerisation of 1-decene. Table 2 also shows the viscosity, viscosity index (VI) and pour point measurements of polyalphaolefin (PAO) lubricating oils. The PAO's are prepared by hydrogenation of the olefinic product resulting from the conventional oligomerisation of alpha-olefins using a BF3-alcohol catalyst. In Table 2, PAO(Feluy) is a commercially available polyalpholefin from Feluy under the tradename Durasyn 164. From Table 2 it can be seen that the lubricating oils of the present invention have higher i.e. superior viscosity index (VI) than the polyalpha-olefins lubricating oils prepared by conventional processes. In the Table the following abbreviations were used:

Me<sub>2</sub>Hex

1,5-dimethylhexyl

**EtHex** 

2-ethylhexyl

Βz

Benzyl

15

10

5

Table 2

Lubricating Oil	Catalyst	Viscosity 40° C	Viscosity	VI	Pour
		(cSt)	100° C		Point
			(cSt)		micro
PAO	BF <sub>3</sub> -alcohol	17.5	4.0	124	-72
PAO (Feluy)	BF <sub>3</sub> -alcohol	17.0	3.9	120	-65
C36 alkene	(Me <sub>2</sub> Hex) <sub>3</sub> TACCl <sub>3</sub> /MAO	18.3	4.3	150	-30
C30 alkene	(Me <sub>2</sub> Hex) <sub>3</sub> TACCl <sub>3</sub> /MAO	12.2	3.2	126	-69
C30 alkene	(EtHex) <sub>3</sub> TACCl <sub>3</sub> /MAO	13.0	3.3	131	not-
					measured
C30 alkene	(Me2Hex) <sub>3</sub> TACCl <sub>3</sub> /MAO	11.8	3.1	130	not
					measured
C30 alkene	(Bz) <sub>3</sub> TACCl <sub>3</sub> /MAO	12.3	3.2	126	not
					measured
C30 alkene	(Bz) <sub>3</sub> TACCl <sub>3</sub> /co-MAO	12.1	3.2	137	-60


#### Claims:

- 1. A process for the oligomerisation of C8-C36 alpha-olefins to give a polyolefin product comprising trimer which process comprises contacting the C8-C36 alpha-olefin with a catalyst in a solvent at a temperature below 20°C wherein the catalyst comprises a complex of a chromium compound and a 1,3,5-triazacyclohexane and the polyolefin product comprises at least 70 mole% of trimer.
- 2. A process according to claim 1 wherein the C8-C36 alpha-olefin is selected from the group consisting of octene-1, decene-1, dodecene-1, hexadecene-1, octadecene-1 and eicosene
- 3. A process according to claim 1 or claim 2 wherein the polyolefin product comprises at least 80% of trimer.
- 4. A process according to claim 3 wherein the polyolefin product comprises at least 90% of trimer.
- 5. A process according to any one of claims 1 to 4 wherein the 1,3,5-triazacyclohexane is of the formula

15

10

5



20

wherein R is a hydrocarbyl group.

6. A process according to claim 5 wherein R is selected from the group consisting

of dimethylhexyl, n-octyl, methylbenzyl, dimethylundecanyl and n-dodecanyl

7. A process according to any one of claims 1 to 6 wherein the catalyst is a complex of a 1,3,5-triazacyclohexane and a chromium halide

- 8. A process according to claim 7 wherein the chromium halide is a chromium chloride.
- 9. A process according to any one of claims 1 to 8 wherein the catalyst additionally comprises an alkyl alumoxane.
- 10. A process according to any one of claims 1 to 9 wherein the process is carried out at a temperature of from -25 to 5°C
- 10 11. A polyolefin product produced by the process of any one of claims 1 to 10
  - 12. A process for producing a lubricating oil wherein said process comprises catalytically hydrogenating a polyolefin product produced by any one of claims 1 to 10
  - 13. Use of a polyolefin product produced according to any one of claims 1 to 10 in the manufacture of a lubricating oil.

15

5

20

25

30

ļ	ification of subject matter C07C2/32 C10G50/02			
I	to International Patent Classification (IPC) or to both national classification	cation and IPC		
	SEARCHED  ocumentation searched (classification system followed by classifica-	Hon eumhala\	d	
IPC 7	C07C C10G	, ,		
	tion searched other than minimum documentation to the extent that			
	lata base consulted during the international search (name of data b	ase and, where practical, search terms used	1)	
	ENTS CONSIDERED TO BE RELEVANT			
Category °	Citation of document, with indication, where appropriate, of the re	olevant passages	Relevant to claim No.	
A	US 5 744 677 A (WU FENG-JUNG) 28 April 1998 (1998-04-28) claims		1	
A	EP 0 583 072 A (BP CHEMICALS) 16 February 1994 (1994-02-16) claims		12,13	
	ner documents are listed in the continuation of box C.	Patent family members are listed	in annex.	
"A" docume consider a filing de "L" docume which i citation "O" docume other n "P" docume	nt which may throw doubts on priority claim(s) or is cited to establish the publication date of another a or other special reason (as specified) ant referring to an oral disclosure, use, exhibition or	To later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention.  "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone.  "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person sidiled in the art.  "&" document member of the same patent family		
	actual completion of the International search	Date of malting of the international sec		
	March 2000	15/03/2000		
Name and m	naling address of the ISA  European Patent Office, P.B. 5818 Patentiaan 2  NL - 2280 HV Rijewijk  Tel. (+31-70) 340-2040, Tx. 31 651 epo ni,	Authorized officer  Van Geyt, J		
	Fex: (+31-70) 340-3016	van deyt, o		

		mation on patent family mem	PCT/GB 99/04010			
Patent document cited in search report	Publication date		Patent family member(s)		Publication date	
US 5744677	A	28-04-1998	US US CA DE DE EP JP	5968866 A 5550305 A 5811618 A 2079399 A 69212761 D 69212761 T 0537609 A 5221882 A	19-10-1999 27-08-1996 22-09-1998 17-04-1993 19-09-1996 02-01-1997 21-04-1993 31-08-1993	
EP 0583072	A	16-02-1994	CA CN DE DE DK JP NO US ZA	2100704 A 1081705 A,B 69315274 D 69315274 T 583072 T 6172759 A 932705 A 5382739 A 9305130 A	29-01-1994 09-02-1994 02-01-1998 12-03-1998 22-12-1997 21-06-1994 31-01-1994 17-01-1995	